
EB-L720U

DATASHEET / BROCHURE





A powerful high brightness laser display with versatile connectivity, the EB-L720U is an ideal display solution for effective collaboration.

The EB-L720U delivers exceptional image quality, focussing on professional content delivery and display performance. Designed around ease of use, up to a 500" display size, affordability and sustainability, it's the ideal imaging solution for today's professional world.

Featuring a powerful 7,000 lumens high-brightness capability, along with Full HD, WUXGA, 16:6 wide screen, support for 4K input and detail enhancement technology, it gives users brighter, more vivid displays of up to 500".

Providing more premium features than you would typically expect to find in this display class, the EB-L720U delivers edge-blending and rich geometric correction to achieve one seamless large-format display. And for multimedia content, you can playback content without any lagging, and create playlists and set schedules directly from USB memory, all thanks to H.264 advanced video coding and the Epson Content Manager.

Flexibility is another hallmark of this display solution - a split-screen function allows two or four images from different sources to be combined in one large display; wired or optional wireless¹ with support for Miracast¹ makes connectivity simple and straightforward; and HDBaseT content can be shared and distributed without compromising on quality.

Thanks to the renowned market leading² reliability of Epson laser displays, this fit and forget solution eliminates the need for regular maintenance. And for added confidence the EB-L720U comes with a standard 3-year warranty to provide lasting peace of mind.

KEY FEATURES

- High brightness, scalable size Provides 7,000 lumens high-brightness display at up to 500"
- Premium display features Full HD, 4K support, edge-blending and geometric correction
- Unrestricted viewing Free from pixilation, glare, fingerprints and a central bevel
- Social distancing support Scalable display meets the needs of every audience configuration
- Plug, click and collaborate Collaborate using Epson's wireless presentation system - ELPWP10
- Legal Statement

Complies with The UK Product Security and Telecommunications Infrastructure (Product Security) requirements. Epson will provide security updates for 7 years from purchase



PRODUCT SPECIFICATIONS

TECHNOLOGY	
Projection System	3LCD Technology, RGB liquid crystal shutter
LCD Panel	0.67 inch with C2 Fine
MAGE	
Color Light Output	7,000 Lumen- 4,900 Lumen (economy) In accordance with IDMS15.4
White Light Output	7,000 Lumen - 4,900 Lumen (economy) In accordance with ISO 21118:2020
Resolution	WUXGA
High Definition	Full HD
Aspect Ratio	16:10
Pixel Numbers	2,304,000
Contrast Ratio	5,000,000 : 1
Light source	Laser
Laser Light source	20,000 hours Durability High, 30,000 hours Durability Eco
Keystone Correction	Manual vertical: ± 30 °, Manual horizontal ± 30 °
Colour Video Processing	10 Bits
2D Vertical Refresh Rate	192 Hz - 240 Hz
Colour Reproduction	Upto 1.07 billion colours
OPTICAL	
Throw Ratio	1.35 - 2.20:1
Zoom	Manual, Factor: 1 - 1.6
Lens	Optical
Lens Screen Size	50 inches - 500 inches
Projection Lens F Number	1.5 - 1.7
Projection Lens F Number Projection Lens Focal Length	
Projection Lens Focus	Manual
Offset	27:1
Unser	27.1
CONNECTIVITY	
Interfaces	RS-232C, Ethernet Interface (1000 Base-T/ 100-Base TX/ 10-Base-T), Wireless LAN a/n (5GHz)
	(optional), VGA in (2x), VGA out, HDMI in (2x), HDBaseT, Miracast (optional), Jack plug out,
	Jack plug in (2x), USB 2.0-A, USB 2.0
Epson iProjection App	Ad-Hoc / Infrastructure
ADVANCED FEATURES	
Security	Kensington lock, Padlock, Security cable hole, Wireless LAN unit lock
2D Colour Modes	Dynamic, Cinema, Presentation, sRGB, DICOM SIM
Other features	21:9 aspect ratio support, A/V mute, Arc Correction, Auto source search, Built-in speaker, CEC
	compatible, Edge Blending, Home Screen, Instant on/off, Long light source life, PC Free,
	Power on button, Screen share, Split-Screen-Function, Ultra-wide display (16:6), iProjection
	Арр
Video Color Modes	App Cinema, Dynamic, Presentation, sRGB, DICOM SIM
Video Color Modes Projector control	App Cinema, Dynamic, Presentation, sRGB, DICOM SIM via: AMX, Crestron, Control4, Crestron Integrated Partner, Extron IP Link, Extron XTP, AMX
	App Cinema, Dynamic, Presentation, sRGB, DICOM SIM
	App Cinema, Dynamic, Presentation, sRGB, DICOM SIM via: AMX, Crestron, Control4, Crestron Integrated Partner, Extron IP Link, Extron XTP, AMX
Projector control GENERAL	App Cinema, Dynamic, Presentation, sRGB, DICOM SIM via: AMX, Crestron, Control4, Crestron Integrated Partner, Extron IP Link, Extron XTP, AMX
Projector control	App Cinema, Dynamic, Presentation, sRGB, DICOM SIM via: AMX, Crestron, Control4, Crestron Integrated Partner, Extron IP Link, Extron XTP, AMX Device Discovery, Control4 Simple Device Discovery Protocol 287 Watt (Normal On-Mode), 187 Watt (Eco On-Mode), 345 Watt (Normal Peak-mode), 258
Projector control GENERAL Power consumption	App Cinema, Dynamic, Presentation, sRGB, DICOM SIM via: AMX, Crestron, Control4, Crestron Integrated Partner, Extron IP Link, Extron XTP, AMX Device Discovery, Control4 Simple Device Discovery Protocol 287 Watt (Normal On-Mode), 187 Watt (Eco On-Mode), 345 Watt (Normal Peak-mode), 258 Watt (Eco Peak-Mode), 0.3 Watt (Energy saving standby)
Projector control GENERAL Power consumption Supply Voltage	App Cinema, Dynamic, Presentation, sRGB, DICOM SIM via: AMX, Crestron, Control4, Crestron Integrated Partner, Extron IP Link, Extron XTP, AMX Device Discovery, Control4 Simple Device Discovery Protocol 287 Watt (Normal On-Mode), 187 Watt (Eco On-Mode), 345 Watt (Normal Peak-mode), 258 Watt (Eco Peak-Mode), 0.3 Watt (Energy saving standby) AC 100 V - 240 V, 50 Hz - 60 Hz
Projector control GENERAL Power consumption Supply Voltage Product dimensions	App Cinema, Dynamic, Presentation, sRGB, DICOM SIM via: AMX, Crestron, Control4, Crestron Integrated Partner, Extron IP Link, Extron XTP, AMX Device Discovery, Control4 Simple Device Discovery Protocol 287 Watt (Normal On-Mode), 187 Watt (Eco On-Mode), 345 Watt (Normal Peak-mode), 258 Watt (Eco Peak-Mode), 0.3 Watt (Energy saving standby) AC 100 V - 240 V, 50 Hz - 60 Hz 440 x 122 x 304 mm (Width x Depth x Height)
Projector control GENERAL Power consumption Supply Voltage Product dimensions Product weight	App Cinema, Dynamic, Presentation, sRGB, DICOM SIM via: AMX, Crestron, Control4, Crestron Integrated Partner, Extron IP Link, Extron XTP, AMX Device Discovery, Control4 Simple Device Discovery Protocol 287 Watt (Normal On-Mode), 187 Watt (Eco On-Mode), 345 Watt (Normal Peak-mode), 258 Watt (Eco Peak-Mode), 0.3 Watt (Energy saving standby) AC 100 V - 240 V, 50 Hz - 60 Hz 440 x 122 x 304 mm (Width x Depth x Height) 7.8 kg
Projector control GENERAL Power consumption Supply Voltage Product dimensions Product weight Noise Level	App Cinema, Dynamic, Presentation, sRGB, DICOM SIM via: AMX, Crestron, Control4, Crestron Integrated Partner, Extron IP Link, Extron XTP, AMX Device Discovery, Control4 Simple Device Discovery Protocol 287 Watt (Normal On-Mode), 187 Watt (Eco On-Mode), 345 Watt (Normal Peak-mode), 258 Watt (Eco Peak-Mode), 0.3 Watt (Energy saving standby) AC 100 V - 240 V, 50 Hz - 60 Hz 440 x 122 x 304 mm (Width x Depth x Height)
Projector control GENERAL Power consumption Supply Voltage Product dimensions Product weight Noise Level Supported Temperature	App Cinema, Dynamic, Presentation, sRGB, DICOM SIM via: AMX, Crestron, Control4, Crestron Integrated Partner, Extron IP Link, Extron XTP, AMX Device Discovery, Control4 Simple Device Discovery Protocol 287 Watt (Normal On-Mode), 187 Watt (Eco On-Mode), 345 Watt (Normal Peak-mode), 258 Watt (Eco Peak-Mode), 0.3 Watt (Energy saving standby) AC 100 V - 240 V, 50 Hz - 60 Hz 440 x 122 x 304 mm (Width x Depth x Height) 7.8 kg Normal: 39 dB (A) - Economy: 27 dB (A) Storage -10° C - 60° C
Projector control GENERAL Power consumption Supply Voltage Product dimensions Product weight Noise Level Supported Temperature Supported Humidity	App Cinema, Dynamic, Presentation, sRGB, DICOM SIM via: AMX, Crestron, Control4, Crestron Integrated Partner, Extron IP Link, Extron XTP, AMX Device Discovery, Control4 Simple Device Discovery Protocol 287 Watt (Normal On-Mode), 187 Watt (Eco On-Mode), 345 Watt (Normal Peak-mode), 258 Watt (Eco Peak-Mode), 0.3 Watt (Energy saving standby) AC 100 V - 240 V, 50 Hz - 60 Hz 440 x 122 x 304 mm (Width x Depth x Height) 7.8 kg Normal: 39 dB (A) - Economy: 27 dB (A)
Projector control GENERAL Power consumption Supply Voltage Product dimensions Product weight Noise Level Supported Temperature Supported Humidity Included Software	App Cinema, Dynamic, Presentation, sRGB, DICOM SIM via: AMX, Crestron, Control4, Crestron Integrated Partner, Extron IP Link, Extron XTP, AMX Device Discovery, Control4 Simple Device Discovery Protocol 287 Watt (Normal On-Mode), 187 Watt (Eco On-Mode), 345 Watt (Normal Peak-mode), 258 Watt (Eco Peak-Mode), 0.3 Watt (Energy saving standby) AC 100 V - 240 V, 50 Hz - 60 Hz 440 x 122 x 304 mm (Width x Depth x Height) 7.8 kg Normal: 39 dB (A) - Economy: 27 dB (A) Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90% EasyMP Multi PC Projection
Projector control GENERAL Power consumption Supply Voltage Product dimensions Product weight Noise Level Supported Temperature Supported Humidity Included Software	App Cinema, Dynamic, Presentation, sRGB, DICOM SIM via: AMX, Crestron, Control4, Crestron Integrated Partner, Extron IP Link, Extron XTP, AMX Device Discovery, Control4 Simple Device Discovery Protocol 287 Watt (Normal On-Mode), 187 Watt (Eco On-Mode), 345 Watt (Normal Peak-mode), 258 Watt (Eco Peak-Mode), 0.3 Watt (Energy saving standby) AC 100 V - 240 V, 50 Hz - 60 Hz 440 x 122 x 304 mm (Width x Depth x Height) 7.8 kg Normal: 39 dB (A) - Economy: 27 dB (A) Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90% EasyMP Multi PC Projection Air filter, Ceiling mount, Document camera, External Speaker, HDBaseT Transmitter, Safety
Projector control GENERAL Power consumption Supply Voltage Product dimensions Product weight Noise Level Supported Temperature Supported Humidity ncluded Software	App Cinema, Dynamic, Presentation, sRGB, DICOM SIM via: AMX, Crestron, Control4, Crestron Integrated Partner, Extron IP Link, Extron XTP, AMX Device Discovery, Control4 Simple Device Discovery Protocol 287 Watt (Normal On-Mode), 187 Watt (Eco On-Mode), 345 Watt (Normal Peak-mode), 258 Watt (Eco Peak-Mode), 0.3 Watt (Energy saving standby) AC 100 V - 240 V, 50 Hz - 60 Hz 440 x 122 x 304 mm (Width x Depth x Height) 7.8 kg Normal: 39 dB (A) - Economy: 27 dB (A) Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90% EasyMP Multi PC Projection Air filter, Ceiling mount, Document camera, External Speaker, HDBaseT Transmitter, Safety wire set, Suspension adapter, WP System - ELPWP10, Wireless LAN unit, Wireless
Projector control GENERAL Power consumption Supply Voltage Product dimensions Product weight Noise Level Supported Temperature Supported Humidity Included Software Options	App Cinema, Dynamic, Presentation, sRGB, DICOM SIM via: AMX, Crestron, Control4, Crestron Integrated Partner, Extron IP Link, Extron XTP, AMX Device Discovery, Control4 Simple Device Discovery Protocol 287 Watt (Normal On-Mode), 187 Watt (Eco On-Mode), 345 Watt (Normal Peak-mode), 258 Watt (Eco Peak-Mode), 0.3 Watt (Energy saving standby) AC 100 V - 240 V, 50 Hz - 60 Hz 440 x 122 x 304 mm (Width x Depth x Height) 7.8 kg Normal: 39 dB (A) - Economy: 27 dB (A) Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90% EasyMP Multi PC Projection Air filter, Ceiling mount, Document camera, External Speaker, HDBaseT Transmitter, Safety wire set, Suspension adapter, WP System - ELPWP10, Wireless LAN unit, Wireless transmitter - ELPWT01
Projector control GENERAL Power consumption Supply Voltage Product dimensions Product weight Noise Level Supported Temperature Supported Temperature Supported Humidity Included Software Options Loudspeaker	App Cinema, Dynamic, Presentation, sRGB, DICOM SIM via: AMX, Crestron, Control4, Crestron Integrated Partner, Extron IP Link, Extron XTP, AMX Device Discovery, Control4 Simple Device Discovery Protocol 287 Watt (Normal On-Mode), 187 Watt (Eco On-Mode), 345 Watt (Normal Peak-mode), 258 Watt (Eco Peak-Mode), 0.3 Watt (Energy saving standby) AC 100 V - 240 V, 50 Hz - 60 Hz 440 x 122 x 304 mm (Width x Depth x Height) 7.8 kg Normal: 39 dB (A) - Economy: 27 dB (A) Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90% EasyMP Multi PC Projection Air filter, Ceiling mount, Document camera, External Speaker, HDBaseT Transmitter, Safety wire set, Suspension adapter, WP System - ELPWP10, Wireless LAN unit, Wireless transmitter - ELPWT01 10 Watt
Projector control GENERAL	App Cinema, Dynamic, Presentation, sRGB, DICOM SIM via: AMX, Crestron, Control4, Crestron Integrated Partner, Extron IP Link, Extron XTP, AMX Device Discovery, Control4 Simple Device Discovery Protocol 287 Watt (Normal On-Mode), 187 Watt (Eco On-Mode), 345 Watt (Normal Peak-mode), 258 Watt (Eco Peak-Mode), 0.3 Watt (Energy saving standby) AC 100 V - 240 V, 50 Hz - 60 Hz 440 x 122 x 304 mm (Width x Depth x Height) 7.8 kg Normal: 39 dB (A) - Economy: 27 dB (A) Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90% EasyMP Multi PC Projection Air filter, Ceiling mount, Document camera, External Speaker, HDBaseT Transmitter, Safety wire set, Suspension adapter, WP System - ELPWP10, Wireless LAN unit, Wireless transmitter - ELPWT01 10 Watt Boardroom, Home Office, Large Meeting Room / Auditorium, Meeting room / Classroom,
Projector control GENERAL Power consumption Supply Voltage Product dimensions Product dimensions Product weight Noise Level Supported Temperature Supported Temperature Supported Humidity Included Software Options Loudspeaker Room Type / Application	App Cinema, Dynamic, Presentation, sRGB, DICOM SIM via: AMX, Crestron, Control4, Crestron Integrated Partner, Extron IP Link, Extron XTP, AMX Device Discovery, Control4 Simple Device Discovery Protocol 287 Watt (Normal On-Mode), 187 Watt (Eco On-Mode), 345 Watt (Normal Peak-mode), 258 Watt (Eco Peak-Mode), 0.3 Watt (Energy saving standby) AC 100 V - 240 V, 50 Hz - 60 Hz 440 x 122 x 304 mm (Width x Depth x Height) 7.8 kg Normal: 39 dB (A) - Economy: 27 dB (A) Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90% EasyMP Multi PC Projection Air filter, Ceiling mount, Document camera, External Speaker, HDBaseT Transmitter, Safety wire set, Suspension adapter, WP System - ELPWP10, Wireless LAN unit, Wireless transmitter - ELPWT01 10 Watt Boardroom, Home Office, Large Meeting Room / Auditorium, Meeting room / Classroom, Signage / Retail, Visitor Attraction
Projector control GENERAL Power consumption Supply Voltage Product dimensions Product dimensions Product weight Noise Level Supported Temperature Supported Temperature Supported Humidity included Software Options Loudspeaker Room Type / Application Positioning	App Cinema, Dynamic, Presentation, sRGB, DICOM SIM via: AMX, Crestron, Control4, Crestron Integrated Partner, Extron IP Link, Extron XTP, AMX Device Discovery, Control4 Simple Device Discovery Protocol 287 Watt (Normal On-Mode), 187 Watt (Eco On-Mode), 345 Watt (Normal Peak-mode), 258 Watt (Eco Peak-Mode), 0.3 Watt (Energy saving standby) AC 100 V - 240 V, 50 Hz - 60 Hz 440 x 122 x 304 mm (Width x Depth x Height) 7.8 kg Normal: 39 dB (A) - Economy: 27 dB (A) Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90% EasyMP Multi PC Projection Air filter, Ceiling mount, Document camera, External Speaker, HDBaseT Transmitter, Safety wire set, Suspension adapter, WP System - ELPWP10, Wireless LAN unit, Wireless transmitter - ELPWT01 10 Watt Boardroom, Home Office, Large Meeting Room / Auditorium, Meeting room / Classroom, Signage / Retail, Visitor Attraction Ceiling Mounted, Desktop, Floor, Wall Mounted
Projector control GENERAL Power consumption Supply Voltage Product dimensions Product dimensions Product weight Noise Level Supported Temperature Supported Temperature Supported Humidity Included Software Options Loudspeaker Room Type / Application	App Cinema, Dynamic, Presentation, sRGB, DICOM SIM via: AMX, Crestron, Control4, Crestron Integrated Partner, Extron IP Link, Extron XTP, AMX Device Discovery, Control4 Simple Device Discovery Protocol 287 Watt (Normal On-Mode), 187 Watt (Eco On-Mode), 345 Watt (Normal Peak-mode), 258 Watt (Eco Peak-Mode), 0.3 Watt (Energy saving standby) AC 100 V - 240 V, 50 Hz - 60 Hz 440 x 122 x 304 mm (Width x Depth x Height) 7.8 kg Normal: 39 dB (A) - Economy: 27 dB (A) Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90% EasyMP Multi PC Projection Air filter, Ceiling mount, Document camera, External Speaker, HDBaseT Transmitter, Safety wire set, Suspension adapter, WP System - ELPWP10, Wireless LAN unit, Wireless transmitter - ELPWT01 10 Watt Boardroom, Home Office, Large Meeting Room / Auditorium, Meeting room / Classroom, Signage / Retail, Visitor Attraction
Projector control GENERAL Power consumption Supply Voltage Product dimensions Product dimensions Product weight Noise Level Supported Temperature Supported Temperature Supported Humidity included Software Options Loudspeaker Room Type / Application Positioning	App Cinema, Dynamic, Presentation, sRGB, DICOM SIM via: AMX, Crestron, Control4, Crestron Integrated Partner, Extron IP Link, Extron XTP, AMX Device Discovery, Control4 Simple Device Discovery Protocol 287 Watt (Normal On-Mode), 187 Watt (Eco On-Mode), 345 Watt (Normal Peak-mode), 258 Watt (Eco Peak-Mode), 0.3 Watt (Energy saving standby) AC 100 V - 240 V, 50 Hz - 60 Hz 440 x 122 x 304 mm (Width x Depth x Height) 7.8 kg Normal: 39 dB (A) - Economy: 27 dB (A) Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90% EasyMP Multi PC Projection Air filter, Ceiling mount, Document camera, External Speaker, HDBaseT Transmitter, Safety wire set, Suspension adapter, WP System - ELPWP10, Wireless LAN unit, Wireless transmitter - ELPWT01 10 Watt Boardroom, Home Office, Large Meeting Room / Auditorium, Meeting room / Classroom, Signage / Retail, Visitor Attraction Ceiling Mounted, Desktop, Floor, Wall Mounted
Projector control GENERAL Power consumption Supply Voltage Product dimensions Product weight Noise Level Supported Temperature Supported Humidity Included Software Options Loudspeaker Room Type / Application Positioning Colour	App Cinema, Dynamic, Presentation, sRGB, DICOM SIM via: AMX, Crestron, Control4, Crestron Integrated Partner, Extron IP Link, Extron XTP, AMX Device Discovery, Control4 Simple Device Discovery Protocol 287 Watt (Normal On-Mode), 187 Watt (Eco On-Mode), 345 Watt (Normal Peak-mode), 258 Watt (Eco Peak-Mode), 0.3 Watt (Energy saving standby) AC 100 V - 240 V, 50 Hz - 60 Hz 440 x 122 x 304 mm (Width x Depth x Height) 7.8 kg Normal: 39 dB (A) - Economy: 27 dB (A) Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90% EasyMP Multi PC Projection Air filter, Ceiling mount, Document camera, External Speaker, HDBaseT Transmitter, Safety wire set, Suspension adapter, WP System - ELPWP10, Wireless LAN unit, Wireless transmitter - ELPWT01 10 Watt Boardroom, Home Office, Large Meeting Room / Auditorium, Meeting room / Classroom, Signage / Retail, Visitor Attraction Ceiling Mounted, Desktop, Floor, Wall Mounted

EB-L720U

WHAT'S IN THE BOX

• Remote control incl. batteries

EPSON[®]

- Power cable
- User guide
- Warranty Documents
- HDMI Cable

OPTIONAL ACCESSORIES

- Ceiling Pipe (450mm) ELPFP13 V12H003P13
- Ceiling Pipe (700mm) ELPFP14 V12H003P14
- Active Speakers (2 x 15W) ELPSP02 V12H467040DA
- Air Filter ELPAF56 L600/EB-14XX Series V13H134A56
- Safety Wire ELPWR01
 V12H003W01
- Adapter ELPAP11 Wireless LAN (5GHz) V12H005A01
- Ceiling Mount (White) ELPMB22 V12H003B22
- Ceiling Mount (Low profile) ELPMB30 V12H526040
- Ceiling Mount ELPMB68
 V12H006AE0

LOGISTICS INFORMATION

SKU V11HA44040 EAN code 8715946695587 Country of Origin China

Wireless Presentation Systems

- Epson ELPWP10 Wireless Presentation System V12HA41040
- Epson ELPWP20 Wireless Presentation System V12HA42040

Visualizers

- ELPDC30
- V12HB09080
- ELPDC07
- V12H759040 • ELPDC13
- V12H757040DA • ELPDC21
- V12H758040DA

EB-L720U

Wireless and Miracast are enabled when used with the optional ELPAP11 adapter.
 2.

 2. 2001 to 2020, 500-lumen and above, excluding screenless TVs, Futuresource Consulting – Quarterly Projector Market Insights – Worldwide Analyzer CY20Q4.

Home users: 0343 90 37766 Business users¹: 0871 42 37766 Republic of Ireland: 01 436 7742 Or visit us at https://www.epson.co.uk/contactus * 10p per minute plus network extras.

For more information please contact:

Web: www.epson.co.uk www.epson.ie

EPSON[®]

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners. Product information is subject to change without prior notice. Last extracted: 2022-08-23