



# KODAK

## Rapid-Dry Photographic Satin Paper, 190g

# Produce posters faster than ever

### Instant dry-time

KODAK Rapid-Dry Photographic Satin Paper, 190g is a genuine resin-coated paper that provides excellent image quality and instant dry times with dye and pigment inks.

### Excellent color density

Turn out posters and signage faster than you can say “tradeshow graphics” with KODAK’s Rapid-Dry wide-format media. Outstanding color density and wide color gamut give you breathtaking image quality. Innovative microporous coatings make for fast dry times, which means less chance of smearing and waste, and the ability to apply laminates instantly.

### FSC®-certified

Meet environmental objectives with this FSC®-certified paper.

### FEATURES:

- Microporous, instant-dry coating
- Superior image quality, wide color gamut, enhanced density and sharpness
- Thermal and cold laminate compatible
- FSC®-certified paper

### APPLICATIONS:

- High-end posters and signage
- Photo enlargements
- Point of purchase graphics and displays

US Size	Euro Size	Quantity	SKU
24" x 100'	61,0 cm x 30,5 m	1 Roll	222737-00B
36" x 100'	91,4 cm x 30,5 m	1 Roll	222738-00B
42" x 100'	106,7 cm x 30,5 m	1 Roll	222739-00B
60" x 100'	152,4 cm x 30,5 m	1 Roll	222741-00B



# KODAK

## Rapid-Dry Photographic Satin Paper, 190g

Properties	Specifications
<b>Material</b>	Resin-coated photo paper
<b>Gauge</b>	8 mil, 190g
<b>CIE Whiteness</b>	107
<b>Environmental</b>	FSC®-certified paper
<b>Opacity</b>	>90
<b>Tint (CIE L*a*b*)</b>	93.0, -0.4, -3.0
<b>Delta b*</b>	0.8
<b>Software Setting</b>	The coating is engineered for more than 300% ink coverage. A photo gloss, satin or semi-gloss setting is recommended as a starting point. However, a custom ICC profile is ideal for optimal results.
<b>Light Fastness</b>	Inkjet ink fading time is based on the inks you use and the print display environment. Dye-based inks fade noticeably under direct sunlight and interior applications where direct sunlight may fall on the image, and/or where fluorescent or other UV lighting is present. Though fading is inherent in all inkjet inks, certain UV-resistant inks, pigment-based inks, and UV-inhibiting coatings will extend image longevity. For light-fastness data and to determine an ink's suitability for the application, contact the ink manufacturer.
<b>Finishing/Post Processing</b>	It is recommended that you protect the printed side by mounting under glass, laminating, clear coating, or using photographic sleeves. This will help ensure image durability and stability. Pressure sensitive laminates provide the best bond. Applying the laminate by hand is not recommended.
<b>Handling Recommendations</b>	Avoid touching the coated surface and use cotton gloves when handling inkjet coated materials. Rolls of Kodak inkjet media come with the coated side facing out.
<b>Ideal Storage Conditions</b>	70° F (21° C), 50% R.H. (a controlled environment is recommended); store in original packaging
<b>Shelf Life</b>	1 year from the BMG ship date when stored in proper conditions.



The mark of responsible forestry



AMS: 888-893-4668  
EMEA: +34 935 479 700  
APJ: +61 2 8038 5013

**KODAKWFMedia.com**

The KODAK trademark, logo, and trade dress are used under license from KODAK.

© 2023, Brand Management Group

